

Flexible LED Strip



General

Product Type:	LED Flexible Strip
Mounting Type:	Mounted/ Recessed
Driver Required:	Yes
Application:	Indoor

Lighting

Light Source:	LED SMD
Wattage:	14.4W/m
Lumen:	1400lm/m @3500K
Efficacy (lm/w):	100lm/W
Beam Angle	120°
Colour Temp (K):	3000K/3500K/4000K
CRI (Ra):	90
LED Qty:	60LED/m
Macadam Ellipse:	<2 SDCM
Lifetime (hrs):	50000 hrs



Electrical


Input:	24Vdc
Driver Type:	Remote
Dimmable:	No (Optional)
Power Feed:	One/two end feed
Cable Out:	-

Physical

Material:	Polyimide
Finish:	White
Dimension:	W10xH02mm
Min. Cutting Length:	100 mm
Max. Length:	30 m
IP Rating:	IP20
IK Rating:	-
Adjustability:	No
Gross Weight:	0.71 Kg

Additional Information

Warranty:	5 Years
Accessories:	24Vdc drivers and mounting accessories to be ordered separately



Microlights® reserves the right to modify technical specifications and data without notice. Rated values (at 25°C) for luminous flux and electrical load have an initial tolerance of +/- 10%, CCT tolerance ranges from +/- 150K. For product inquiries, please contact us at info@microlightsgroup.ae

©2024 Microlights Lighting LLC. All rights reserved.